

Coslight Polymer Li-ion Battery (For Mass Production)

Model	Nominal Capacity (mAh) Discharge	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA411037	125	3.7	4.1	10.5	37.5
CA421040	130	3.7	4.2	10.5	40.5
CA661119	75	3.7	6.6	11.5	19.5
CA381223	65	3.7	3.8	12.5	23.5
CA701327	150	3.7	7.6	13.5	27.5
CA651329	150	3.7	6.5	13.5	29.5
CA551430	160	3.7	5.5	14.5	30.5
CA621518	110	3.7	6.2	15.5	18.5
CA401550	260	3.7	4.0	15.5	50.5
CA801730	300	3.7	8.0	17.5	30.5
CA631823	210	3.7	6.3	18.5	23.5
CA481922	140	3.7	4.8	19.5	22.5
CA402025	150	3.7	4.0	20.5	25.5
CA552025	150	3.7	5.5	20.5	25.5
CA482030	250	3.7	5.0	20.5	30.5
CA702030	350	3.7	7.0	20.5	30.5
CA7823189	3600	3.7	7.8	23.5	189.5
CA553045	650	3.7	5.5	30.5	45.5
CA503048	700	3.7	5.0	30.5	48.5
CA703048	1000	3.7	7.0	30.5	48.5
CA103048	1500	3.7	10	30.5	48.5
CA323450	550	3.7	3.2	34.5	50.5
CA383450	680	3.7	3.9	34.5	50.5
CA453450	800	3.7	4.5	34.5	50.5
CA553450	1060	3.7	5.5	34.5	50.5
CA383456	700	3.7	3.8	34.5	56.5
CA503456	1000	3.7	5.0	34.5	56.5
CA853465	1900	3.7	8.5	34.5	65.5
CA653495	2400	3.7	6.5	34.5	95.5
CA553553	1150	3.7	5.5	35.5	53.5
CA523635	620	3.7	5.2	36.5	35.5
CA803681	2550	3.7	8.0	36.5	81.5
CA883681	2900	3.7	8.8	36.5	81.5
CA603696	2150	3.7	5.8	36.5	96.5
CA583726	530	3.7	5.8	37.5	26.5
CA503759	1200	3.7	5.0	37.5	59.5
CA553759	1400	3.7	5.5	37.5	59.5
CA603759	1500	3.7	6.4	37.5	59.5
CA753783	2700	3.7	7.5	37.5	83.5
CA403946	930	3.7	4.3	39.5	46.5
CA503946	1030	3.7	5.0	39.5	46.5
CA503965	1500	3.7	5.0	39.5	65.5
CA454061	1280	3.7	4.5	40.5	61.5
CA604071	2000	3.7	6.0	40.5	71.5
CA754090	2900	3.7	7.5	40.5	90.5
CA4240A1	1900	3.7	4.2	40.5	101.5
CA544180	2000	3.7	5.4	41.5	80.5
CA4841120	2600	3.7	4.8	41.5	120.5
CA6041120	3000	3.7	6.0	41.5	120.5
CA414257	1000	3.7	4.1	42.5	57.5
CA6542C2	3700	3.7	6.5	42.5	122.5
CA604355	1500	3.7	6.0	43.5	55.5
CA664364	1900	3.7	6.8	43.5	64.5
CA104462	2000	3.7	10.0	44.5	62.5

CA854475	3000	3.7	8.5	44.5	75.5
CA354556	900	3.7	3.5	45.5	56.5
CA624640	1300	3.7	6.2	46.5	40.5
CA524642	1300	3.7	5.4	46.5	42.5
CA7446102	3900	3.7	7.4	46.5	102.5
CA454780	2000	3.7	4.5	47.5	80.5
CA644845	1450	3.7	6.4	48.5	45.5
CA354860	1300	3.7	3.8	48.5	60.5
CA454870	1700	3.7	4.5	48.5	70.5
CA564889	2700	3.7	5.6	48.5	89.5
CA624932	1000	3.7	6.2	49.5	32.5
CA705065	2400	3.7	7.0	50.5	65.5
CA385085	1800	3.7	4.0	50.5	85.5
CA455085	2100	3.7	4.5	50.5	85.5
CA435186	2000	3.7	4.3	51.5	86.5
CA655186	3000	3.7	6.5	51.5	86.5
CA555335	1150	3.7	5.7	53.5	35.5
CA295357	800	3.7	2.9	53.5	57.5
CA485383	2100	3.7	4.8	53.5	83.5
CA305585	1300	3.7	3.0	55.5	85.5
CA3558120	2800	3.7	3.5	58.5	120.5
CA456248	1480	3.7	4.5	62.5	48.5
CA357173	1700	3.7	3.5	71.5	73.5
CA476394	2800	3.7	4.7	63.5	94.5
CA466548	1550	3.7	4.6	65.5	48.5
CA556850	1800	3.7	5.5	68.5	50.5
CA577070	3200	3.7	5.7	70.5	70.5
CA4070107	3300	3.7	4.0	70.5	107.5
CA387166	2100	3.7	4.1	71.5	66.5
CA287554	1200	3.7	2.8	75.5	54.5
CA397647	1530	3.7	3.9	76.5	47.5
CA447670	2500	3.7	4.4	76.5	70.5
CA387681	2600	3.7	3.8	76.5	81.5
CA588260	3150	3.7	5.8	82.5	60.5

Coslight Polymer Li-ion Battery (UL Certification)

Model	Nominal Capacity (mAh) Discharge current:0.2C	Voltage (V)	Dimension (mm)		
			Thickness Tolerance(+0/-0.5)	Width Tolerance(+0/-1.0)	Height Tolerance(+0/-1.0)
CA042458	440	3.7	4.0	24.5	58.5
CA043048	600	3.7	4.0	30.5	48.5
CA051235	120	3.7	5.0	12.5	35.5
CA065065	2000	3.7	6.0	50.5	65.5
CA0748130	4000	3.7	7.0	48.5	130.5
CA1051138	5000	3.7	10.0	51.5	138.5
CA293559	500	3.7	2.9	35.5	59.5
CA323757	600	3.7	3.2	37.5	57.5
CA383562	780	3.7	3.8	35.5	62.5
CA423456	760	3.7	4.2	34.5	56.5
CA423466	850	3.7	4.2	34.5	66.5
CA443155	660	3.7	4.4	31.5	55.5
CA453451	740	3.7	4.5	34.5	51.5
CA455051	1200	3.7	4.5	50.5	51.5
CA482030	220	3.7	4.8	20.5	30.5
CA496065	2000	3.7	4.9	60.5	65.5
CA523757	1050	3.7	5.2	37.5	57.5
CA5852146	4500	3.7	5.8	52.5	146.5

CA383450	680	3.7	3.8	34.5	50.5
CA041430	120	3.7	4.0	14.5	30.5
CA042030	160	3.7	4.0	20.5	30.5
CA051024	60	3.7	5.0	10.5	24.5
CA051235	160	3.7	5.0	12.5	35.5
CA051322	70	3.7	5.0	13.5	22.5
CA254160	600	3.7	2.5	41.5	60.5
CA381319	50	3.7	3.8	13.5	19.5
CA381632	140	3.7	3.8	16.5	32.5
CA387166	2100	3.7	3.8	71.5	66.5
CA387681	2600	3.7	3.8	76.5	81.5
CA421032	90	3.7	4.2	10.5	32.5
CA421318	55	3.7	4.2	13.5	18.5
CA432035	190	3.7	4.3	20.5	35.5
CA447670	2500	3.7	4.4	76.5	70.5
CA451135	120	3.7	4.5	11.5	35.5
CA451319	60	3.7	4.5	13.5	19.5
CA551230	140	3.7	5.5	12.5	30.5
CA401522	90	3.7	4.0	15.5	22.5
CA588260	3150	3.7	5.8	82.5	60.5
CA303048	400	3.7	3.0	30.5	48.5
CA603759	1500	3.7	6.0	37.5	59.5
CA583726	530	3.7	5.8	37.5	26.5
CA401550	260	3.7	4.0	15.5	50.5
CA401040	110	3.7	4.0	10.5	40.5
CA504080	1800	3.7	5.0	40.5	80.5
CA287554	1200	3.7	2.8	75.5	54.5
CA397647	1450	3.7	3.9	76.5	47.5
CA476145	1250	3.7	4.7	61.5	45.5
CA4741122	2500	3.7	4.7	41.5	122.5
CA421040	135	3.7	4.2	10.5	40.5
CA381223	70	3.7	3.8	12.5	23.5
CA501220	90	3.7	5.0	12.5	20.5
CA411037	125	3.7	4.1	10.5	37.5
CA682839	750	3.7	6.8	28.5	39.5
CA401230	100	3.7	4.0	12.5	30.5
CA511023	90	3.7	5.1	10.5	23.5
CA583761	1150	3.7	5.8	37.5	61.5
CA582237	390	3.7	5.8	22.5	37.5
CA522173	700	3.7	5.2	21.5	73.5
CA363830	330	3.7	3.6	38.5	30.5
CA354239	550	3.7	3.5	42.5	39.5
CA311620	50	3.7	3.1	16.5	20.5
CA383759	970	3.7	3.8	37.5	59.5
CA702030	350	3.7	7.0	20.5	30.5
CA752840	800	3.7	7.5	28.5	40.5
CA462849	530	3.7	4.6	28.5	49.5
CA651329	150	3.7	6.5	13.5	29.5
CA501621	120	3.7	5.0	16.5	21.5
CA351643	170	3.7	3.5	16.5	43.5
CA581730	250	3.7	5.8	17.5	30.5
CA385085	1800	3.7	3.8	50.5	85.5
CA553450	1060	3.7	5.5	34.5	50.5
CA544180	2000	3.7	5.4	41.5	80.5
CA485383	2100	3.7	4.8	53.5	83.5
CA672543	730	3.7	6.7	25.5	43.5
CA273232	220	3.7	2.7	32.5	32.5
CA556850	1950	3.7	5.5	68.5	50.5
CA453759	1190	3.7	4.5	37.5	59.5

CA354951	880	3.7	3.5	49.5	51.5
CA501430	160	3.7	5.0	14.5	30.5
CA422436	320	3.7	4.2	24.5	36.5
CA511023	100	3.7	5.1	10.5	23.5
CA403946	930	3.7	4.3	39.5	46.5
CA604364	1900	3.7	6.0	43.5	64.5
CA323450	550	3.7	3.2	34.5	50.5
CA541227	105	3.7	5.4	12.5	27.5
CA601055	300	3.7	6.0	10.5	55.5
CA761327	150	3.7	7.6	13.5	27.5
CA661119	75	3.7	6.6	11.5	19.5
CA581833	240	3.7	5.8	18.5	33.5
CA043043	500	3.7	4.0	30.5	43.5
CA603696	2150	3.7	6.0	36.5	96.5
CA383456	700	3.7	3.8	34.5	56.5
CA293450	500	3.7	2.9	34.5	50.5
CA7823189	3600	3.7	7.8	23.5	189.5
CA454870	1650	3.7	4.5	48.5	70.5
CA503868	1400	3.7	5.0	38.5	68.5
CA405095	1900	3.7	4.0	50.5	95.5
CA3558120	2800	3.7	3.5	58.5	120.5
CA503759	1300	3.7	5.0	37.5	59.5
CA523635	620	3.7	5.2	36.5	35.5
CA454061	1280	3.7	4.5	40.5	61.5
CA624640	1300	3.7	6.2	46.5	40.5
CA456248	1480	3.7	4.5	62.5	48.5
CA577070	3200	3.7	5.7	70.5	70.5
CA7446102	3800	3.7	7.4	46.5	102.5
CA371125	60	3.7	3.7	11.5	25.5
CA621518	100	3.7	6.2	15.5	18.5
CA313036	300	3.7	3.1	30.5	36.5
CA453450	800	3.7	4.5	34.5	50.5
CA564889	2700	3.7	5.6	48.5	89.5
CA4070107	3300	3.7	4.0	70.5	107.5
CA605172	2400	3.7	6.0	51.5	72.5
CA584169	1800	3.7	5.8	41.5	69.5
CA053946	1030	3.7	5.0	39.5	46.5
CA455085	2100	3.7	4.5	50.5	85.5
CA853465	1950	3.7	8.5	34.5	65.5
CA103048	1500	3.7	10.0	30.5	48.5
CA083048	1200	3.7	8.0	30.5	48.5
CA753783	2700	3.7	7.5	37.5	83.5
CA883681	2900	3.7	8.8	36.5	81.5
CA476394	2800	3.7	4.7	63.5	94.5
CA644845	1450	3.7	6.4	48.5	45.5
CA624932	1000	3.7	6.2	49.5	32.5
CA295357	800	3.7	2.9	53.5	57.5
CA631823	210	3.7	6.3	18.5	23.5
CA625289	3300	3.7	6.2	52.5	89.5
CA702929	520	3.7	7.0	29.5	29.5
CA553759	1400	3.7	5.5	37.5	59.5
CA354860	1300	3.7	3.5	48.5	60.5
CA354556	900	3.7	3.5	45.5	56.5
CA606168	2600	3.7	6.0	61.5	68.5